

SPECIFICATIONS

Chetak® WATER COOLED DIESEL ENGINE (DOUBLE CYLINDER)

Sr. No.	Model No.	Type	Rated Output HP(Kw)	Rated Speed (RPM)	Bore x Stroke (mm)
1	STV-2	BT, GOP, BGC, HFW, LOFOS	15 (11)	1500	87.5 X 110
2	SDM-17	BT, GOP, BGC, HFW, LOFOS	17 (12.5)	1500	95 X 110
3	SDM-20	BT, GOP, BGC, HFW, LOFOS	20 (14.7)	1500	102 X 116
4	SGW-22	TRB, GOP, BGC, HFW, LOFOS	22 (16.2)	1500	102 X 125
5	SDM-26	BT, GOP, BGC, HFW, LOFOS	26 (19.11)	1500	114.3 X 116
6	SDM-28	BT, GOP, BGC, HFW, LOFOS	28 (20.6)	1500	114.3 X 116
7	SGW-28	TRB, GOP, BGC, HFW, LOFOS	28 (20.6)	1500	114.3 X 125
8	SDM-30	BT, GOP, BGC, HFW, LOFOS	30 (22.05)	1500	120 X 116
9	SGW-30	TRB, GOP, BGC, HFW, LOFOS	30 (22.05)	1500	120 X 125

- TRB : Taper Roller Bearing
- HFW : Heavy Fly Wheel
- BT : Bush Type
- GOP : Gear Oil Pump
- BGC : Big Gear Cover
- LOFOS : Lubricating Oil Filter Outside
- SG : Steel Gear Set (optional)
- HD : Heavy Duty

Rotation – Clockwise (Optional – Anti Clockwise) | **Governing** Class B-1 (Optional Class A-2)

OPTIONAL ACCESSORIES

- GER – Gear End Radiator
- CWP – Cooling Water Pump With V-belt Driven
- Electric Start Kit With Battery Charging Alternator ,Battery Cable And Key Starting Panel Board (without Battery)
- 3 Bearing In Selected Models
- VSC – Variable Speed Control
- HSD RR – Half Speed Drive With Taper Housing Reverse Rotation (Anti-Clockwise)

APPLICATIONS



Agriculture



Industrial



Power Generation



Construction

**All images, specifications & colors of products may vary from illustrations and can be changed due to product enhancement.*