

SPECIFICATIONS

Ghetak® WATER COOLED GENERATOR SET

Sr. No.	Model No.	Rated Output (HP)	kVA	Rated Speed (RPM)	Max. Amp.	
					1 Phase/ 240 Volts	3 Phase/ 415 Volts
1	SMPP-35	3.5	2.5	1500	10	—
2	SMPP-5	5	3.5	1500	14	—
3	SAV-1	5	3.5	1500	14	—
4	STV-1	8	5	1500	20	6.7
5	SDM-85	8.5	5	1500	20	6.7
6	SRDM-85	8.5	5	1500	20	6.7
7	SDM-85 (HD)	8.5	5	1500	20	6.7
8	SDM-10	10	7.5	1500	31	10.3
9	SRDM-10	10	7.5	1500	31	10.3
10	SDM-10 (HD)	10	7.5	1500	31	10.3
11	SGW-10 (HD)	10	7.5	1500	31	10.3
12	SRDM-125 (102)	12.5	7.5 / 8.75	1500	31	10.3
13	SDM-125	12.5	10	1500	41	13.7
14	SRDM-125	12.5	10	1500	41	13.7
15	SDM-125 (HD)	12.5	10	1500	41	13.7
16	SGW-125 (HD)	12.5	10	1500	41	13.7
17	SRDM-14 (114.3)	14	10	1500	41	13.7
18	SDM-14	14	10	1500	41	13.7
19	SGW-14 (HD)	14	10	1500	41	13.7
20	SDM-16	16	12.5	1500	52	17.3
21	SGW-16	16	12.5	1500	52	17.3
22	STV-2	15	10	1500	41	13.7
23	SDM-17	17	12.5	1500	52	17.3
24	SDM-20	20	15	1500	62	20.7
25	SGW-22	22	15	1500	62	20.7
26	SDM-26	26	20	1500	83	27.7
27	SDM-28	28	20	1500	83	27.7
28	SGW-28	28	20	1500	83	27.7
29	SDM-30	30	25	1500	---	33.3
30	SGW-30	30	25	1500	---	33.3

SINGLE CYLINDER

DOUBLE CYLINDER

OTHER SPECIFICATIONS

- Single Phase : 240 Volts | 1500 RPM | 50 Hz | 4 Pole | 1.0 Power Factor
- Three Phase : 415 Volts | 1500 RPM | 50 Hz | 4 Pole | 0.8 Power Factor
- Governing Class : B-1 / A-2
- Circulating Cooling Water Pump instead of Radiator for specific requirements.

APPLICATIONS



Agriculture



Industrial



Power Generation



Construction

*All images, specifications & colors of products may vary from illustrations and can be changed due to product enhancement.