

SPECIFICATIONS

Chetak® AIR COOLED GENERATOR SET

Sr. No.	Model No.	Rated Output (HP)	kVA	Rated Speed (RPM)	Max. Amp.	
					1 Phase/ 240 Volts	3 Phase/ 415 Volts
1	SAA-35	3.5	2.5	1500	10	---
2	SAA-50	5	3.5	1500	14	---
3	SAA-75	7.5	5	1500	20	6.7
4	SCAF-1	5	3.5	1500	14	6.7
5	SCAF-8	8	5	1500	20	6.7
6	SCAF-8 (95)	8	5	1500	20	6.7
7	SRCAF-8	8	5	1500	20	6.7
8	SDAF-8	8	5	1500	20	6.7
9	SCAF-10	10	7.5	1500	31	10.3
10	SRCAF-10	10	7.5	1500	31	10.3
11	SDAF-10	10	7.5	1500	31	10.3
12	SGA-10 (HD)	10	7.5	1500	31	10.3
13	SRCAF-12 (102)	10	7.5	1500	31	10.3
14	SCAF-12	12	10	1500	41	13.7
15	SRCAF-12	12	10	1500	41	13.7
16	SDAF-12	12	10	1500	41	13.7
17	SGA-12 (HD)	12	10	1500	41	13.7
18	SRCAF-14 (114.3)	14	10	1500	41	13.7
19	SDDA-14	14	10	1500	41	13.7
20	SGA-14 (HD)	14	10	1500	41	13.7
21	STAF-2	14	10	1500	41	13.7
22	SDA-16	16	12.5	1500	52	17.3
23	SDA-20	20	15	1500	62	20.7
24	SGA-22	22	15	1500	62	20.7
25	SDA-26	26	20	1500	83	27.7
26	SDA-28	28	20	1500	83	27.7
27	SGA-28	28	20	1500	83	27.7

SINGLE CYLINDER

DOUBLE CYLINDER

OTHER SPECIFICATIONS

- Single Phase : 240 Volts | 1500 RPM | 50 Hz | 4 Pole | 1.0 Power Factor
- Three Phase : 415 Volts | 1500 RPM | 50 Hz | 4 Pole | 0.8 Power Factor
- Governing Class : B-1 / A-2

APPLICATIONS




Agriculture



Industrial



Power Generation



Construction

*All images, specifications & colors of products may vary from illustrations and can be changed due to product enhancement.